

Armour System – RapidPair™ Configuration Software



KEY FEATURES:

- User friendly “drag and drop” interface
- Wireless communication to SCAN~LINK devices
- Compatible with most versions of Microsoft Windows
- Download data
- Troubleshoot and service

The RapidPair™ tool allows the user to configure, maintain, and monitor the SCAN-LINK Armour System™. The RapidPair™ software provides a visual means to quickly pair devices together by forming a connection between devices that are required to communicate with each other. Devices that can be paired together are found by RapidPair™ and displayed on the screen. The RapidPair™ software allows for the pairing and configuration of both the SCAN~LINK Antenna and Display Units, as well as for configuration of the SCAN~LINK Tag Health Tester.

RapidPair™ is used to retrieve important and valuable data collected from the antenna unit which is installed on the vehicle. The type of data collected from a SCAN-LINK equipped vehicle is

- number of detections
- time and date of detection
- apparel type and tag type
- as well as whether the safety vest was facing forward or backward

SPECIFICATIONS:

SYSTEM REQUIREMENTS

Operating System	Windows 10 (32 and 64-bit)	RAM	1Gb (min)
	Windows 8 (32 and 64-bit)	HDD	50Mb free (min)
	Windows 7 (32 and 64-bit)	Ports	1x USB 2.0
	Windows Vista (32 and 64-bit)		
	Windows XP (32-bit)		

ELECTRICAL (RPD-SN220 USB Dongle)

System Voltage	5VDC (USB bus powered)	Current	100mA max.
Wireless Link	2405-2475MHz Unlicensed ISM Band, 0.098W EIRP		
Contains	IC ID: 9084A-SM220 Under Synapse Wireless Inc.		
	FCC ID: U90-SM220 Under Synapse Wireless Inc.		
	IFT ID: 201801A01279 Under Synapse Wireless Inc.		